

## PERFORMANCE STATEMENT

### 002DDMP

#### 1 – Unique identification code for product / type:

Glazed dry pressed ceramic tiles with water absorption greater than 10% ( $E_b > 10,0\%$ ), GL

#### 2 – Use:

For internal wall finishes

#### 3 – Name and address of manufacturer:

Revigrés, Indústria de Revestimentos de Grés, Lda.

Apartado 1

3754-001 Barrô (Águeda)

Portugal

[www.revigres.com](http://www.revigres.com)

#### 4 – System of assessment and checking for regularity of applicable performance:

System 4

#### 5 – Performance declared:

<u>Essential characteristics</u>	<u>Performance</u>	<u>Standard</u>
Reaction to fire	A1	EN 14411:2012 (Group BIII GL)
Release of dangerous substances, for: - Cadmium (Cd) - Lead (Pb)	NPD NPD	
Modulus of rupture:	$\geq 12 \text{ N/mm}^2$	
Bond strength/adhesion, for:	NPD	
Resistance to thermal shock	Resistant	
Durability, for: - Internal use	Compliant	

NPD – Non Stated Performance. It is stated for each case, on client's request.

This performance statement has been issued under the responsibility of the manufacturer identified in point 3.

Quality Department



Rui Vasco  
27.06.2014