

PERFORMANCE STATEMENT

002DDGP

1 – Unique identification code for product / type:

Glazed or unglazed dry pressed ceramic tiles, with water absorption less than 0.5% ($E_b \leq 0.5\%$).

2 – Use:

For internal or external, floor and wall.

3 – Name and address of manufacturer:

Revigrés, Indústria de Revestimentos de Grés, Lda.
 Apartado 1
 3754-001 Barrô (Águeda)
 Portugal
www.revigres.com

4 – System of assessment and checking for regularity of applicable performance:

System 4

5 – Performance declared:

<u>Essential characteristics</u>	<u>Performance</u>	<u>Standard</u>
Reaction to fire	A1 and A1 _{FL}	EN 14411:2012 (Group B1a GL or UGL)
Release of dangerous substances, for: - Cadmium (Cd) - Lead (Pb)	NPD NPD	
Bending strength: - Thickness < 7,5mm ≥ 7,5mm	> 1500 N > 2000 N	
Bond strenght/adhesion, for:	NPD	
Slippage	NPD	
Resistance to thermal shock	Resistant	
Tactility:	NPD	
Durability, for: - Internal use - External use (resistance to frost)	Compliant Compliant	

NPD – Non Stated Performance. It is stated for each case, on client’s request.

This performance statement has been issued under the responsibility of the manufacturer identified in point 3.

Quality Department



Rui Vasco
27.06.2014