

KERAMA MARAZZI

Limited Liability Company "Kerama Marazzi"
 5, Italianskaya Str., Orel, Russia 302024
 Tel.: +7 (4862) 49-98-10
 Fax.: +7 (4862) 49-98-32
 E-mail: plant@kerama-marazzi.ru
 www.kerama-marazzi.com



Out.No 279 09.02.2017

TECHNICAL SPECIFICATION

Collection	Trade mark	Size (cm)	Thickness (mm)
Sansevero	KERAMA MARAZZI	9,9x9,9	7

Nominal size: (N) 9,9x9,9cm	
1268S	Sansevero black
1267S	Sansevero white

Corresponds with standard EN 14411:2012 annex G group Bla – GL
Corresponds with standard Technical Conditions TC 5752-012-04693313-2009
Intended for internal and external floorings & wall finishes

Technical Features	Testing Method	Meas. unit	Standard	Actual average values
PHISICAL PROPERTIES				
Water absorption	EN ISO 10545-3	(%)	Eb ≤ 0,5	0,3
Modulus of rupture	EN ISO 10545-4	(N/mm ²)	min 35	41
Wear resistance, PEI	EN ISO 10545-7	class	1 min – 5 max	3
Thermal shock resistance	EN ISO 10545-9		withstand	satisfy
Frost resistance	EN ISO 10545-12	(cycles)	not less 100	120
CHEMICAL PROPERTIES				
Resistance to chemicals for household use and swimming pool salts	EN ISO 10545-13		min GB	GA
Resistance to low concentration acids and bases	EN ISO 10545-13		specified by the manufacturer	GLA
Stain resistance	EN ISO 10545-14		min class 3	satisfy
ANTISLIPPERY PROPERTIES				
Dynamic coefficient of friction	B.C.R.A.		μ ≥ 0,40	μ ≥ 0,40

Manufactured by the company LLC "Kerama Marazzi"
 5, Italianskaya st., Orel, Russia, 302024

Standardization and certification engineer



Polezhaeva O.A.