



## DECLARATION OF PERFORMANCE

No. 002\_CasalgrPad

1. Unique identification code of the product type:  
**Dry-pressed ceramic tiles, with water absorption  $0,5\% < E_b \leq 3\%$**
2. Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $0,5\% < E_b \leq 3\%$**
3. Intended use(s)  
**For internal walls and floorings**
4. Name or registered trade mark, and contact address of the manufacturer  
**Casalgrande Padana SpA, Via Statale 467,73 Casalgrande (RE)**
5. N.A.
6. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
7. Name and identification number of notified laboratory, if relevant N.A.  
Task(s) carried out N.A.  
AVCP system N.A.  
Document issued and date of issue N.A.
8. N.A.
9. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	<b>Based on the decision 96/603/CE and its changes</b>             <b>EN 14411:2012</b>
<b>Release of dangerous substance, for:</b>		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength $\geq 7.5$ mm	> 1 100 N	
Breaking strength Thickness < 7.5 mm	> 700 N	
Slipperiness**	NPD	
Tactility***	NPD	
<b>Bond strength/adhesion, for:</b>		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
<b>Durability for:</b>		
- internal use:	Pass	
- external use: freeze-thaw resistance	NPD	
<p>* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations  **Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.  ***Only for tactile floorings, meaning if requested for blind and visually impaired: as a description of the surface</p>		

10. The performance of the product identified in point 1 is in conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

ING. GABRIELE BORGHI (TECHNICAL SERVICE)

Name and function

CASALGRANDE (RE) 01/07/2013  
Place and date of issue

Signature



**Casalgrande Padana SpA,**  
**42013 Via Statale 467,73 Casalgrande (RE)**

05

**002\_CasalgrPad**

**EN 14411:2012**

Dry-pressed ceramic tiles, with water absorption  $0,5 = E_b \leq 3$  % for internal walls and floorings

<b>Reaction to fire</b>	A1 <sub>FL</sub>
<b>Release of dangerous substances, for:</b>	
- Cadmium*	NPD
- Lead*	NPD
<b>Breaking strength</b>	> 1100 N
<b>Slipperiness**, as:</b>	
PTV slider 57, CEN/TS 16165:2011 Annex C	NPD
<b>Durability for:</b>	
- Internal use:	Pass
- External use: freeze-thaw resistance	NPD

\* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations

\*\*Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.