



BASIC CHARACTERISTICS:

Pieces name:	BLANCO BRILLO (AZJ) 30X90 RC /ARG04_S
Size (cm.):	30X90 RECTIFIED
Colour:	BLANCO
Series name:	BLANCOS 30X90
Family:	GLAZED WALL TILES

TECHNICAL CHARACTERISTICS:

Fabrication process:	Single-fired porous white-body tile	
Absorption group (ISO 13006):	BIII	
Finish:	Glazed (GL)	
Body:	White Body	
Surface Finish:	Gloss	
Work size (mm):	300 x 900 x 8,7	
Aesthetic classification and shade variations:	V.0	
Diferent design number:	UNICA	
Facial dimension range and surface quality:	Complies with the standard	UNE EN ISO 10545-2

PHYSICAL CHARACTERISTICS:

Water absorption:	E>10%	UNE EN ISO 10545-3
Braking strenght (S):	> 600N	UNE EN ISO 10545-4
Flexural tensile strenght (N/mm2):	≥15 N/mm2	

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





Lineal thermal expansion between 20° to 100°C	Complies with the standard	UNE EN ISO 10545-8
Thermic shock resistance:	Complies with the standard	UNE EN ISO 10545-9
Crazing resistance:	Complies with the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	Not apply	UNE EN ISO 10545-12

CHEMICAL PROPERTIES:

Resistance to chemicals and pool treatment products:	Complies with the standard	UNE EN ISO 10545-13
Resistance to High concentration acids and bases:	HA	
Resistance to Low concentration acids and bases:	LA	
Resistance to staining:	Complies with the standard	UNE EN ISO 10545-14

CE MARKING:

CE	003CPR-A/11-4-2013
----	--------------------

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:

